

# SID



ابزارهای پژوهش



سرویس ترجمه تخصصی



کارگاه‌های آموزشی



بلاگ مرکز اطلاعات علمی



سامانه ویراستاری STES



فیلم‌های آموزشی

سامانه ویراستاری (ویرایش متون فارسی، انگلیسی، عربی)

کارگاه‌ها و فیلم‌های آموزشی مرکز اطلاعات علمی



روش تحقیق کمی

روش تحقیق کمی



آموزش مهارت‌های کاربردی در تدوین و چاپ مقالات ISI

آموزش مهارت‌های کاربردی در تدوین و چاپ مقالات ISI



آموزش نرم افزار Word برای پژوهشگران

آموزش نرم افزار Word برای پژوهشگران

---

۱\*

( / / : // : )

× mm<sup>2</sup>

( / )

( )

( )

( )

(

)

Archive of SID

Chaharmahali et al. (2008)

(Morton & Lossi, 2003)

Morton & Lossi, )

(2003

Archive of SID

Kazemi-Najafi et )

al., 2006; Espert et al., 2004; Khavkine et al.,  
Malvar et al., ) (2001; Han, 1998

Khavkine et al., 2001; ) (2001

U.V (Anonymous, 2003

(Anonymous, 2003)

+ /

Tajvidi et al. (2006) .

MAPP (%)  
( )

g / min

SI-080

rpm

WPC-

kg) g/10min

(MAPP)

( ) ( )

/ ( = °C = /

% (HCl)

% (NaClO)

Scharlau

(NaOH)

Scharlau

±

±

( )

Applichem

ASTM

\* \*

D

\* \*

%

± °C

(%)

(%)

(%)

PW  
PWM

(C°)

(rpm)

...

$$WA (w') = \frac{W_o' - W_w}{W_o'} \times 100 \quad ($$

(g) WA(w') %  
 (g) W<sub>o'</sub> %  
 (g) W<sub>w</sub> %

( )

cm

mm/min

D543-95

ASTM

ASTM

D7031-4

(MOR)

(MOE)

DARTEC

± °C

kN

/ g

ASTM

D256

( )

IZOD

J/m

/ g

$$WA (w) = \frac{W_w - W_o}{W_o} \times 100 \quad ($$

)

(

W<sub>w</sub> (g)

WA(w)

W<sub>o</sub>


(g)

± °C


<sup>1</sup> Un-notched

( )  
)


(



MAPP



MAPP




MAPP

P	F
/	/
/	/
/	/

MAPP


MAPP

MAPP




MAPP

( )





( )



Archive

MAPP  
MAPP

MAPP

MAPP

MAPP

---

( )

( )

MAPP

MAPP

MAPP

( )

Tajvidi et al. (2006)

Chaharmahali et al. (2008)

MAPP

(Thwe & Liao, 2003; Taib et al., 2006)

(Sjöström, 1981)

(Sjöström, 1981)

MAPP

Myers et al.(2006)

Thwe & Liao, )

(2003

COOH

(Thwe &Liao, 2003)

MAPP

( )

(Stark & Rowlands, 2003)

MAPP

MAPP

MAPP

Oksman & Clemons 1997; )

Rozman et al., 2001; Thwe & Liao,2003;

MAPP (Sombatsompap et al.,2005

Liao et al., 1999; Karama et )

(al., 1993; Kajorncheappunnegam et al., 2003

)

(

Sanadi et al., 1995; Sain )

(et al., 2005

---

<sup>1</sup> Decomposition

---

## References

- American Society for Testing and Materials. 1990. ASTM D256- 90b, Standard Test Methods for Determining the Izod Pendulum Impact Resistance of Plastics, West Conshohocken, Pa. USA.
- American Society for Testing and Materials. 1996. ASTM D543-95 Evaluating the Resistance of Plastics to Chemical Reagents, West Conshohocken, Pa. USA.
- American Society for Testing and Materials. 2004. Standard Guide for Evaluating Mechanical and Physical Properties of Wood – Plastic Composite Products ASTM D 7031 – 04 .West Conshohocken, Pa, USA.
- Anonymous, 2003. Wood plastic composite Study-Technologies and UK Market Opportunities, Research Report, UK .82p
- Chaharmahali, M., Kazemi Najafi, S. and Tajvidi, M. 2008. Chemical Resistance of Natural Fiber/ High Density Polyethylene (HDPE) composites, Iranian Journal of Natural Resources, 61(1):133-141
- Espert, A., Vilaplana, F. and Karlsson S. 2004. Comparison of Water Absorption in Natural Cellulosic Fibers from Wood and one-year Crops in Polypropylene Composites and its Influence on their Mechanical Properties, Journal of Composites Part A, 35: 126776.
- Han, J.S. 1998. Properties of Nonwood fibers. Proceedings of the Korean Society of Wood Science and Technology Annual Meeting, The Korean Society of Science and Technology, Seoul, Korea. 3-12
- Kajorncheappunngam, S., Gupta, R.K. and Rao, H.V.S. 2002. Effect of Aging Environment on Degradation of Glass-reinforced Epoxy, Journal of Composite for Construction, 6(1): 61-69 9pp.
- Karama, M., Touratier, M. and Pegoraro, P. 1993. Test of Accelerated Aging Composites Material in Shipbuilding, Proceedings of the 9th International Conference on Composite Materials, ICCM/9-Madrid,5: 532-539
- Kazemi Najafi, S. Tajvidi, M., and Chaharmahali, M. 2006. A Study on the Long Term Water Uptake Behavior of Lignocellulosic-High Density Polyethylene Composites. Journal of Applied Polymer Science, 102: 3907-3911.
- Khavkine, M., Kazayawoko, M., Low, S. and Balatineez, J.J. 2001. Durability of wood Flour thermoplastic composites under extreme environmental condition and fungal exposure, International Journal of Polymeric Materials, 26: 255-269.
- Liao, K., Shultheisz, C.R. and Hunston, D.L. 1999. Effects of Environmental Aging on the Properties of Pultruded GFRP, Composites Part B, 30(5): 485-493.
- Malvar L. J., Pendleton, D.E., Tichy, R. 2001. Fire issues in engineered wood composites for naval waterfront facilities. Sample Journal, 37(4): 70-75..
- Myers, T. J., Kytomaa, H. K. and Smith, T. R. 2006. Environmental Stress- Corrosion Cracking of Fiberglass: Lessons learned From Failures in the Chemical industry. Journal of Hazardous Materials, 142: 695-704..
- Morton, J. and Rossi, L. 2003 Current and Emerging Applications for Natural and Wood fiber Composites, The 7<sup>th</sup> International conference of wood fiber-plastic composites, Madison. May 19-20.
- Oksman, K., and Clemons, C. 1997. Mechanical Properties and Morphology of Impact Modified Polypropylene-Wood Flour Composites, Journal of Applied Polymer Science, 67(9): 1503-1513.
- Rozman, H.D., Tay, G.S., Kumar, R.N., Abusamah, A., Ismail, H. and Ishak, Z.A.M. 2001. Polypropylene-Oil palm empty Fruit Bunch-Glass Fiber Hybrid Composites: a Preliminary Study on the Flexural and Tensile Properties, European Polymer Journal, 37: 1283-1291..
- Sain, M., Suhara, P., Law, S. and Bloulooux, A. 2005. Interface Modification and Mechanical Properties of Natural Fiber-Polyolefin Composite Products, Journal of Reinforced Plastics and Composites, 24(2): 121-130.
- Sanadi, A.R., Caulfield, D.F., Rodney, E., Jacobson, R.E. and Rowell, R.M. 1995. Renewable Agricultural Fibers as Reinforcing Fillers in Plastics: Mechanical Properties of Kenaf Fiber-Polypropylene Composites, Journal of Industrial and Engineering Chemistry Research, 34(5): 1889-1897.
- Sjöström, E. 1981. Wood chemistry; fundamental and applications. Academic Press, New York. 233p

...

- 
- Sombatsompop, N., Yotinwattanakumtorn, C. and Thongpin, C. 2005. Influence of Type and Concentration of Maleic Anhydride Grafted Polypropylene and Impact Modifiers on Mechanical Properties of PP/Wood Sawdust Composites, *Journal of Applied Polymer Science*, 97(2): 475-484
  - Stark, N.M. and Rowlands, R.E. 2003. Effects of Wood Fiber Characteristics on Mechanical Properties of Wood/Polypropylene Composites, *Wood and Fiber Science*, 35(2): 167-174..
  - Tajvidi, M., Kazemi Najafi, S., Shekaraby, M.M. and Motiee, N. 2006. Effect of Chemical Reagents on The Mechanical Properties of Natural Fiber Polypropylene Composites, *Polymer Composites*, 27(5): 563-569.
  - Taib, R.M., Mohd Ishak, Z.A., Rozman, H.D. and Glasser, W.G. 2006. Effect of Moisture Absorption on the Tensile Properties of Steam-exploded *Acacia mangium* Fiber Polypropylene Composites, *Journal of Thermoplastic Composite Materials Composites*, 19(5): 475-489..
  - Thwe, M.M. and Liao K. 2003. Durability of Bamboo-Glass Fiber Reinforced Polymer Matrix Hybrid Composites, *Composites Science and Technology*, 63(3-4): 375-38712pp.

Archive of SID

## Effect of Chemical Reagents on Physical and Mechanical Properties of Wood Flour-Polypropylene Composites

S. Kazemi Najafi<sup>\*1</sup>, A. Nasiri Avanaki<sup>2</sup> and R. Behrooz<sup>3</sup>

<sup>1</sup> Associate Prof., Wood Science and Technology Department, Tarbiat Modares University, I.R. Iran

<sup>2</sup> Master's Degree Graduate, Wood Science and Technology Department, Tarbiat Modares University, I.R. Iran

<sup>3</sup> Assistant Professor, Wood Science and Technology Department, Tarbiat Modares University, I.R. Iran

(Received: 18 August 2009, Accepted: 26 December 2011)

### Abstract

In this research, the effects of different chemical reagents on physical and mechanical properties of wood flour-polypropylene composites were investigated. For this purpose, wood flour and polypropylene were compounded (at 50% fiber loading) in a counter-rotating twin-screw extruder in the presence or absence of MAPP to produce the composites. The nominal cross section of the manufactured composites was 70\*10 mm<sup>2</sup>. The specimens were immersed in NaOH (10%), HCl (10 %) and NaClO (2 %). After one week of immersion, the specimens were oven-dried and changes of oven-dried weight and mechanical properties (flexural modulus, flexural strength and un-notched impact strength) were determined. The mechanical properties of the composites immersed in chemical solutions were compared with the non-immersed composites (as control). From the results, the composites immersed in NaOH exhibited higher oven dried weight whereas those immersed in HCl and NaClO exhibited lower oven dried weights. All chemical reagents significantly reduced the mechanical properties of the composites. The addition of 2% MAPP could not considerably reduce the effect of chemical reagents on mechanical properties of studied formulations.

**Keywords:** Wood flour-polypropylene composites, NaOH, HCl, NaClO, physical and mechanical properties

# SID



ابزارهای پژوهش



سرویس ترجمه تخصصی



کارگاه‌های آموزشی



بلاگ مرکز اطلاعات علمی



سامانه ویراستاری STES



فیلم‌های آموزشی

سامانه ویراستاری (ویرایش متون فارسی، انگلیسی، عربی)

کارگاه‌ها و فیلم‌های آموزشی مرکز اطلاعات علمی



روش تحقیق کمی

روش تحقیق کمی



آموزش مهارت‌های کاربردی در تدوین و چاپ مقالات ISI

آموزش مهارت‌های کاربردی در تدوین و چاپ مقالات ISI



آموزش نرم افزار Word برای پژوهشگران

آموزش نرم افزار Word برای پژوهشگران