

SID



ابزارهای
پژوهش



سرویس ترجمه
تخصصی



کارگاه های
آموزشی



بلاگ
مرکز اطلاعات علمی



سامانه ویراستاری
STES



فیلم های
آموزشی

کارگاه های آموزشی مرکز اطلاعات علمی



آموزش مهارت های کاربردی در تدوین و چاپ مقالات ISI

آموزش مهارت های کاربردی
در تدوین و چاپ مقالات ISI



روش تحقیق کمی

روش تحقیق کمی



آموزش نرم افزار Word برای پژوهشگران

آموزش نرم افزار Word
برای پژوهشگران

Porous Poly Ether Ether Ketone (PEEK) Biomaterial in Critical Bone Defects

Parisa Amdjadi ^{1,2}, Hanieh Nojehdehian ^{1,3}

1. Department of Dental Biomaterials, School of Dentistry, Shahid Beheshti University of Medical Sciences, Tehran, Iran

2. Department of Developmental Sciences, Marquette University, School of Dentistry, Milwaukee, WI, USA

3. Department of Tissue Engineering, School of Advanced Technologies in Medicine, Shahid Beheshti University of Medical Sciences, Tehran, Iran

Corresponding Author: Parisa Amdjadi, E-mail: drfatemi@gmail.com

ABSTRACT

As a new Biomaterial, polyether-ether-ketone (PEEK) has gained widespread acceptance as a high-strength polymer used in hard and soft tissue reconstructions, with favorable imaging compatibility and stiffness that closely matches bone. The ultimate goal of most medical implants is to restore impaired biological function and achieve functional integration with the body. Several porous polymers and other tissue engineered scaffolds have made advances in this regard, however similar solutions in high load-bearing orthopedic environments remain elusive in clinically adopted biomaterials.

The challenge for porous peek material is the engineering of a material with pores that are sufficiently large for bone ingrowth, yet also able to retain desirable structural properties. Porous PEEK implants exhibited increased osseointegration and fixation by improving the migration and proliferation of various cell types to enhance vascular and bone tissue ingrowth.

The findings showed that typical porosity of 51%, Wall Thickness of 312 μ m, and mean pore size of 369 μ m demonstrated improvements in connective density near that of trabecular bone, however low compressive strength (15MPa) would preclude the use of wholly porous material in critical size load bearing application.

Limiting porosity to PEEK's surface could promote osseointegration and maintain bulk mechanical properties. A porous surface layer could retain implant strength, provide an optimum external structure for bone ingrowth, and avoid tissue necrosis at the center of large fully porous implants in cases of limited vascular and nutrient supply. Therefore solid- porous PEEK ,will provide both the structural integrity in load bearing application, along with the ability for osseoconductivity and improved implant fixation.

SID



ابزارهای
پژوهش



سرویس ترجمه
تخصصی



کارگاه های
آموزشی



بلاگ
مرکز اطلاعات علمی



سامانه ویراستاری
STES



فیلم های
آموزشی

کارگاه های آموزشی مرکز اطلاعات علمی



تازه های آموزش
آموزش مهارت های کاربردی در تدوین و چاپ مقالات ISI

آموزش مهارت های کاربردی
در تدوین و چاپ مقالات ISI



تازه های آموزش
روش تحقیق کمی

روش تحقیق کمی



تازه های آموزش
آموزش نرم افزار Word برای پژوهشگران

آموزش نرم افزار Word
برای پژوهشگران